

Schottky Rectifier

■特征 Features

- I_o 3.0A
- VRRM 20V-40V
- 耐正向浪涌电流能力高
- High surge current capability

■用途 Applications

- 整流用 Rectifier

■极限值（绝对最大额定值）

Limiting Values (Absolute Maximum Rating)


参数名称 Item	符号 Symbol	单位 Unit	条件 Conditions	1N58		
				20	21	22
反向重复峰值电压 Repetitive Peak Reverse Voltage	V_{RRM}	V		20	30	40
正向平均电流 Average Forward Current	$I_{F(AV)}$	A	正弦半波 60Hz, 电阻负载, $T_a=50^{\circ}\text{C}$ 60Hz Half-sine wave, Resistance load, $T_a=50^{\circ}\text{C}$	3.0		
正向（不重复）浪涌电流 Surge(Non-repetitive)Forward Current	I_{FSM}	A	正弦半波 60Hz, 一个周期, $T_a=25^{\circ}\text{C}$ 60Hz Half-sine wave, 1 cycle, $T_a=25^{\circ}\text{C}$	80		
结温 Junction Temperature	T_J	$^{\circ}\text{C}$		-55~+125		
储存温度 Storage Temperature	T_{STG}	$^{\circ}\text{C}$		-55 ~ +150		

■电特性（ $T_a=25^{\circ}\text{C}$ 除非另有规定）

Electrical Characteristics ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Condition		1N58		
					20	21	22
正向峰值电压 Peak Forward Voltage	V_{FM}	V	$I_{FM}=3.0A$		0.475	0.5	0.525
反向峰值电流 Peak Reverse Current	I_{RRM1}	mA	$V_{RM}=V_{RRM}$	$T_a=25^{\circ}\text{C}$	1.0		
	I_{RRM2}			$T_a=125^{\circ}\text{C}$	10		
热阻(典型) Thermal Resistance(Typical)	$R_{\theta J-A}$	$^{\circ}\text{C/W}$	结和环境之间 Between junction and ambient		40		
	$R_{\theta J-L}$		结和引线之间 Between junction and lead		10		

■外形尺寸和印记 Outline Dimensions and Mark



■特性曲线（典型） Characteristics(Typical)

